

PFO2810

8ch HDCVI Optical Transceiver (Lite)



Features

- > High definition, real-time
- > Support HDCVI video format 720p/25、720p/30、720p/50、720p/60、1080p/25、1080p/30
- > UPnP, easy installation
- > Metal plate is used for the structure, fully enclosed dustproof design
- > Industrial wide temperature design

PFO2810

Technical Specifications

Model	PFT2810T	PFT2810R
Physical Port	FC (Single-mode fiber)、8*BNC、1*RS485	
Transmission Distance	0-20km	
Input/ Output Wave Length	1310nm / 1550nm	1550nm / 1310nm
Input Auto Cable Balance	1080p: 75-5 coaxial support 300m 720p : 75-5 coaxial support 500m	
Input/Output Impedance	75Ω	
Sampling Bandwidth	10bit	
Power	DC12V	
Power Consumption	<12W	<8W
Application Humidity	10%—90%	
High&Low temperature	- 40℃~70℃	
Weight	630g	
Dimension(W×D×H)	100mm×150mm×42mm	
Installation	DIN rail	

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.