

DH-PFS3106-4T

4-Port Ethernet Switch (Unmanaged)



Features

- 2-layer industrial level switch
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- 100M/1000M self-adaptive SFP fiber port
- Industrial wide temperature design

Technical Specification

| | |
|------------------------|--|
| Model | DH-PFS3106-4T |
| Ethernet Port | 1*100/1000 Base-X 1*10/100/1000 Base-T 4*10/100 Base-T |
| Switching Capacity | 6.8G |
| Packet Forwarding Rate | 3.57Mpps |
| Packet Buffer Memory | 1Mb |
| MAC Table Size | 8K |
| Exchange Mode | Store & forward |
| Application Humidity | 10%-90% |
| Power | DC 12V |
| Power Consumption | ≤3W |
| Lightning Protection | Common Mode 4KV Differential Mode 2KV |
| Working Temperature | -40°C-70°C |
| Weight | 480g |
| Dimension(W×D×H) | 150mm×100mm×30mm |

Accessories

| | |
|---------|--|
| Model | |
| PFT3900 | 155M 850nm,2km,LC, Multi-mode |
| PFT3950 | 1.25G 850nm,500m,LC, Multi-mode |
| PFT3910 | 155M 1310/1550nm,20km,LC, Single-mode |
| PFT3920 | 155M 1550/1310nm,20km,LC, Single-mode |
| PFT3960 | 1.25G 1310/1550nm,20km,LC, Single-mode |
| PFT3970 | 1.25G 1550/1310nm,20km,LC, Single-mode |