

DH-S1000-8TP

8-Port Hi- PoE Switch



Features

- Two-layer Hi-PoE switch
- Port1, 2 support 60W (Hi-PoE), IEEE802.3af and IEEE802.3at standards
- Support IEEE802.3af, IEEE802.3at standard
- MAC auto study and aging, MAC address list capacity is 8K

Technical Specification

Model	DH-S1000-8TP
Ethernet Port	1*1000 Base-X 1*10/100/1000 Base-T 8*10/100 Base-T(PoE power supply)
PoE Power Consumption	port1, 2 support ≤60W (Hi-PoE) port3, 4 support ≤30W port 5, 6, 7, 8 support ≤15.4W Totals≤120W
PoE Protocol	IEEE802.3af, IEEE802.3at
Switching Capacity	7.6G
Packet Forwarding Rate	4.17Mpps
Packet Buffer Memory	1Mb
MAC Table Size	8K
Flow Control	Enable by default
Application Humidity	10%-90%
Power	AC 100~240V
Lightning Protection	Common Mode 4KV Differential Mode 2KV
Working Temperature	-10°C~55°C
Weight	2.66kg
Dimension(WxDxH)	300mm×220mm×44.4mm

Accessories

Model	
PFT3950	1.25G 850nm,500m,LC, Multi-mode
PFT3960	1.25G 1310/1550nm,20km,LC, Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC, Single-mode