

ARC5408/5808C(-C)


Video Alarm Controller



Feature

- 8-ch alarm input, 4-ch alarm output
- Alarm input and output expansion modules, max expand 64x
- 8-ch alarm keypad input
- 1-ch controlled siren (DC12V, 1A) output, 1-ch DC12, 1.5A power output
- 4/8-ch analog video or network video input & 1-ch video output
- 4-ch audio input, 1-ch audio output and 1-ch IP talk, support SATA HDD, local storage and playback, alarm and video review
- Mobile alarm arming/disarming, support wireless remote arming/disarming
- Support 1 group RS485 programming keyboard input
- 5000 log records
- Local GUI & web config
- IP network, PSTN to upload alarm signal
- 3G network alarm function (-C model)

Dimension



Technical Specifications

Model	ARC5408C(-C)	ARC5808C(-C)
Alarm Input	8-ch alarm input	
Alarm Output	4-ch local dry node alarm output	
3G	WCDMA (—C model)	
PSTN Alarm	Support PSTN dial-up alarm	
Tamper Alarm	1 anti-tamper alarm	
Video In	Analog: 4-ch BNC Digital: 4-ch 720P	Analog: 8-ch BNC Digital: 8-ch 720P
Video Out	1-ch HDMI, 1-ch VGA, 1-ch BNC (1.0Vp-p,75ohms)	
Video Encode Standard	H.264	
Monitor image quality	960H、720P@25fps	
Playback Image quality	960H、720P@25fps	
Playback	Analog: Support 1、2、3、4 Synchronous playback Digital: Max 4-ch 720P	
Motion Detect	Each screen can set 396 (22 × 18) detection areas; multi-level sensitivity, 1-6 optional	
Region Masking	4 regions for each channel	
Audio coding standard	G.711A	
Audio In	Analog: 4-ch Linear audio input Digital: 4-ch IPC Composite audio input	
Audio Out	1-ch BNC (Multiplex audio talk)	
Audio talk	1-ch Two-way talk	
RS485	1-ch, support alarm expansion and alarm keypad	
USB	1 USB2.0	
Cable Network	1-ch 10/100M Ethernet, RJ45	
HDD	1 SATA, Max.4T	
Battery Powered	12V 7A	
Supply	AC220V 50Hz	
Power	<10W (No HDD)	
Working environment	-10°C~+55°C	
Overall dimensions	350×350×95mm	
Weight	<5.5Kg	
Installation	Wall mount	

ARC5408/5808C(-C)
