

## ASR1101A/ASR1001A/ASR110A-D/ASR1001A-D

### RFID Reader



ASR1101A/ASR1001A  
ASR1101A-D/ASR1001A-D

### Features

- > RS-485/Wiegand protocol
- > Default IC (Mifare) card("-D" means ID EM card)
- > Support card, password
- > Sensitive touch keypad with blue backlight
- > Watch dog function ensure device free from halting
- > Beep and indicator
- > Surface mounted installation

# ASR1101A/ASR1001A/ASR110A-D/ASR1001A-D

## Technical Specifications

Model	ASR1101A/ASR1101A-D	ASR1001A/ ASR1001A-D
<b>System</b>		
Main Processor	8 Bit	
<b>Read</b>		
Read Format	13.56MHz(Mifare)/125KHz("-D" EM, Optional)	
Read Range	6-8cm (max.)	
Response time	<0.1s	
<b>Function</b>		
Tamper Alarm	Yes	
<b>Interface</b>		
To Controller	RS485	Wiegand
<b>General</b>		
Keypad	12Key(0-9,*,#) Sensitive touch keypad	
LCD Display	Blue backlight	
Beep Tone	Buzzer	
Ingress protection	IP55	
Power Supply	9-15VDC/100mA	
Working Environment	-30°C - +60°C	
Working Humidity	≤95%	
Dimension(W×D×H)	135mm*86mm*12mm	
Weight	0.25Kg	

### Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

\*Design and specifications are subject to change without notice.

© 2015 Dahua Technology Co., Ltd.