

DH-IPC-HDBW2531R-ZS/VFS

5MP WDR IR Dome Network Camera



- 1/2.7" 5Megapixel progressive CMOS
- H.265 & H.264 dual-stream encoding
- 20fps@5M(2592×1944)&25/30fps@3M(2304×1296)
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- Micro SD card slot, up to 128GB
- 2.7~13.5mm varifocal lens
- Max IR LEDs Length 30m
- IP67, IK10, PoE



System Overview

The IR Megapixel Vari-focal camera delivers 2MP/4MP/5MP resolution with a 2.7mm – 13.5mm varifocal lens. The camera's elegant blend of aesthetics combined with a range of easy mounting solutions provides an excellent choice for a variety of small to mid-size applications at an affordable price.

Functions

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

Wide Dynamic Range (WDR)

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, true WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Smart IR Technology

With IR illumination, detailed images can be captured in low light or total darkness. The camera's Smart IR technology adjusts the intensity of camera's infrared LEDs to compensate the distance of an object. Smart IR technology prevents IR LEDs from whitening out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 30m (98ft).

Protection (IP67, IK10, wide voltage)

The camera allows for ±10% input voltage tolerance, suitable for the

most unstable conditions for outdoor applications. Its 2KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), the camera is the choice for installation in even the most unforgiving environments.

Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -30° C to +60° C (-22° F to +140° F) with 95% humidity.

Image flip

Capturing unnecessary data such as surrounding hallway walls can increase storage requirements without any added value. The image flip feature allows the camera's image to be rotated in 90° increments for better video optimization.

Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

Technical Specification

Camera

| | |
|--------------------------|--|
| Image Sensor | 1/2.7" 5Megapixel progressive CMOS |
| Effective Pixels | 2592(H) x1944(V) |
| RAM/ROM | 512MB/32MB |
| Scanning System | Progressive |
| Electronic Shutter Speed | Auto/Manual, 1/3~1/100000s |
| Minimum Illumination | 0.02Lux/F1.6(Color,1/3s,30IRE) 0.2Lux/F1.6(Color,1/30s,30IRE) 0Lux/F2.0(IR on) |
| S/N Ratio | More than 50dB |
| IR Distance | Distance up to 30m(98ft) |
| IR On/Off Control | Auto/ Manual |
| IR LEDs | 2 |

Lens

| | | | | | |
|----------------------|-----------------------------|-------------|------------|------------|-----------|
| Lens Type | Motorized(-ZS),Manual(-VFS) | | | | |
| Mount Type | Board-in | | | | |
| Focal Length | 2.7mm~13.5mm | | | | |
| Max. Aperture | F1.6 | | | | |
| Angle of View | H:95°~27°, V:70°~20° | | | | |
| Focus Control | Motorized(-ZS),Manual(-VFS) | | | | |
| Close Focus Distance | 0.3m | | | | |
| DORI Distance | Lens | Detect | Observe | Recognize | Identify |
| | W | 64m(210ft) | 26m(85ft) | 13m(43ft) | 6m(20ft) |
| | T | 222m(728ft) | 89m(292ft) | 44m(144ft) | 22m(72ft) |

PTZ

| | |
|----------------|---|
| Pan/Tilt Range | Pan:0° ~355° ;Tilt:0° ~75° ;Rotation:0° ~355° |
|----------------|---|

Video

| | |
|----------------------|--|
| Compression | H.265+/H.265/H.264+/H.264 |
| Streaming Capability | 2 Streams |
| Resolution | 5M(2592x1944)/4M(2688x1520)/ (2560x1440)/(2304x1296)/1080P(1920x1080)/ SXGA(1280x1024)/1.3M(1280x 960)/720P(1280x720)/D1(704x576/704x480)/ VGA(640x480)/CIF(352x288/352x240) |
| Frame Rate | 5M (1 ~ 20fps)/3M(1 ~ 25/30fps) D1/CIF(1 ~ 20/25fps) |
| Bit Rate Control | CBR/VBR |
| Bit Rate | H.265: 12K ~ 8448Kbps H.264: 32K ~ 10240Kbps |
| Day/Night | Auto(ICR) / Color / B/W |
| BLC Mode | BLC / HLC / WDR(120dB) |

| | |
|-------------------------------------|---|
| White Balance | Auto/Natural/Street Lamp/Outdoor/Manual |
| Gain Control | Auto/Manual |
| Noise Reduction | 3D DNR |
| Motion Detetion | Off / On (4 Zone, Rectangle) |
| Region of Interest | Off / On (4 Zone) |
| Electronic Image Stabilization(EIS) | N/A |
| Smart IR | Support |
| Digital Zoom | 16x |
| Flip | 0°/90°/180°/270° |
| Mirror | Off / On |
| Privacy Masking | Off / On (4 Area, Rectangle) |

Audio

| | |
|-------------|-----|
| Compression | N/A |
|-------------|-----|

Network

| | |
|---------------------|---|
| Ethernet | RJ-45 (10/100Base-T) |
| Protocol | HTTP;TCP;ARP;RTSP;RTP;UDP;RTCP;SMTP;FTP;DHCP ;DNS;DDNS;PPPOE;IPv4/v6;SNMP;QoS;UPnP;NTP |
| Interoperability | ONVIF, PSIA, CGI |
| Streaming Method | Unicast / Multicast |
| Max. User Access | 10 Users / 20 Users |
| Edge Storage | NAS Local PC for instant recording Micro SD Card 128GB |
| Web Viewer | IE, Chrome, Firefox, Safari |
| Management Software | Smart PSS, DSS, Easy4ip |
| Smart Phone | IOS, Android |

Certifications

| | |
|----------------|--|
| Certifications | CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B |
|----------------|--|

Interface

| | |
|-----------------|-----|
| Video Interface | N/A |
| Audio Interface | N/A |
| RS485 | N/A |
| Alarm | N/A |

Electrical

| | |
|-------------------|------------------------------|
| Power Supply | DC12V PoE (802.3af)(Class 0) |
| Power Consumption | <6.2W(-ZS), <4.9W(-VFS) |

Environmental

| | |
|----------------------|---|
| Operating Conditions | -30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH |
| Storage Conditions | -30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH |
| Ingress Protection | IP67 |
| Vandal Resistance | IK10 |

Construction

| | |
|--------------|----------------------------|
| Casing | Metal |
| Dimensions | φ122mm×88.9mm(4.80"×3.50") |
| Net Weight | 0.4Kg (0.88lb) |
| Gross Weight | 0.54Kg(1.19lb) |

Ordering Information

| Type | Part Number | Description |
|------------------------|-----------------------|--------------------------------------|
| 4MP camera | DH-IPC-HDBW2531RP-ZS | 5MP WDR IR Dome Network Camera, PAL |
| | DH-IPC-HDBW2531RN-ZS | 5MP WDR IR Dome Network Camera, NTSC |
| | IPC-HDBW2531RP-ZS | 5MP WDR IR Dome Network Camera, PAL |
| | IPC-HDBW2531RN-ZS | 5MP WDR IR Dome Network Camera, NTSC |
| | DH-IPC-HDBW2531RP-VFS | 5MP WDR IR Dome Network Camera, PAL |
| | DH-IPC-HDBW2531RN-VFS | 5MP WDR IR Dome Network Camera, NTSC |
| | IPC-HDBW2531RP-VFS | 5MP WDR IR Dome Network Camera, PAL |
| | IPC-HDBW2531RN-VFS | 5MP WDR IR Dome Network Camera, NTSC |
| Accessories (optional) | PFA137 | Junction box |
| | PFB203W | Wall mount |
| | PFA152-E | Pole mount |
| | PFB200C | In-ceiling Mount |
| | PFA200W | Rain shade |

Accessories

Optional:



| Junction Mount | Inceiling Mount |
|----------------------------|----------------------------|
| PFA137 | PFB200C |
| | |
| Wall Mount | Pole Mount |
| PFB203W | PFB203W + PFA152-E |
| | |
| Wall Mount with Rain Shade | Pole Mount with Rain Shade |
| PFB203W+PFA200W | PFB203W + PFA152-E+PFA200W |
| | |

Dimensions (mm/inch)

