

DH-NVR3204V-P/3208V-P/3216V-P

4/8/16 Channel 2HDD 4PoE Vertical Network Video Recorder



Features

- > Up to 4/8/16 channel with 1080P realtime live view
- > H.264/MJPEG dual codec decoding
- > Max 120fps@1080P, 240fps@720P, 480fps@D1 preview & recording
- > All channel simultaneous realtime playback, GRID interface
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc.
- > ONVIF Version 2.0 conformance
- > 3D intelligent positioning with Dahua PTZ camera
- > Support 2 SATA HDDs up to 8TB, 1 eSATA up to 16TB,3 USB2.0
- > Support IPC UPnP, 4PoE ports
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DH-NVR3204V-P/3208V-P/3216V-P


Technical Specifications

| Model | DH-NVR3204V-P | DH-NVR3208V-P | DH-NVR3216V-P |
|------------------------------------|---|---------------|---------------|
| System | | | |
| Main Processor | Dual-core embedded processor | | |
| Operating System | Embedded LINUX | | |
| Video & Audio | | | |
| IP Camera Input | 4 channel | 8 channel | 16 channel |
| Two-way Talk | 1channel Input, 1channel Output, RCA | | |
| Display | | | |
| Interface | 1 HDMI, 1 VGA | | |
| Resolution | 1920×1080, 1280×1024, 1280×720, 1024×768 | | |
| Display Split | 1/4 | 1/4/8/9 | 1/4/8/9/16 |
| OSD | Camera title, Time, Video loss, Camera lock, Motion detection, Recording | | |
| Recording | | | |
| Compression | H.264 / MJPEG | | |
| Resolution | 1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480) & etc. | | |
| Record Rate | 100/120fps@1080p, 200/240fps@720p , 400/480fps@D1& etc. | | |
| Bit Rate | 48~ 8192kbps | | |
| Record Mode | Manual, Schedule(Regular(Continuous), MD, Alarm), Stop | | |
| Record Interval | 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec | | |
| Video Detection & Alarm | | | |
| Trigger Events | Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips | | |
| Video Detection | Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank | | |
| Alarm Input | 3 channel | | |
| Relay Output | 1 channel | | |
| Playback & Backup | | | |
| Sync Playback | 1/4 | 1/4/9 | 1/4/9/16 |
| Search Mode | Time/Date, Alarm, MD & Exact search (accurate to second), Smart search | | |
| Playback Function | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom | | |
| Backup Mode | USB Device / eSATA Device / Network | | |
| Network | | | |
| Ethernet | 1 RJ-45 port (10/100/1000Mbps) | | |
| PoE | 4 ports (IEEE802.3af) | | |
| Network Function | HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS etc) | | |
| Max. User Access | 20 users | | |
| Smart Phone | iPhone, iPad, Android, Windows Phone | | |
| Storage | | | |

DH-NVR3204V-P/3208V-P/3216V-P

| | |
|----------------------------|--|
| Internal HDD | 2 SATA ports, up to 8TB, Raid (redundancy) |
| External HDD | 1 eSATA port |
| Auxiliary Interface | |
| USB Interface | 3 ports (1 Rear), USB2.0 |
| RS232 | 1 port, For PC communication & Keyboard |
| RS485 | 1 port, For PTZ control |
| General | |
| Power Supply | NVR: DC12V/5A |
| | PoE: DC48V/1.04A |
| Power Consumption | NVR: 20W (without HDD) |
| | PoE: Max.15W (each) |
| Working Environment | -10°C~+55°C/10%~90%RH/86~106kpa |
| Dimension (W×D×H) | 100mm×220mm×146mm |
| Weight | 1.6kg (without HDD) |

System Connection



* Take NVR3216V-P as an example

Dahua Technology Co., Ltd.

1187BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2013 Dahua Technology Co., Ltd.