



# DHI-NVR5832/5864-I

32/64Channel 2U WizMind Network Video Recorder





Launched by Dahua Technology, Dahua WizMind is a full portfolio of solutions composed of project-oriented products including IPC, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, WizMind provides precise, reliable and comprehensive AI solutions for verticals.

# **System Overview**

Dahua new NVR5000-I network video recorder delivers excellent performance and high recording quality that is ideally suitable for IP video surveillance applications. This NVR adopts powerful processor, providing the capability of 4K resolution processing for applications where image details are highly required. Additionally, the NVR can be served as edge storage, central storage or backup storage with an intuitive shortcut operation menu for remote management and control.

With build-in deep learning module, NVR5000-I series products adopt video image structuring technology based on deep learning algorithms, achieving high-precision human face recognition and perimeter protection. By applying deep learning artificial intelligence, NVR5000-I allows users to focus on what matters most, improves event response time and helps make video actionable.

The NVR is compatible with numerous third-party devices, which make it the perfect solution for surveillance systems that work independently of video management system (VMS).

### **Functions**

### **Perimeter Protection**

Automatically filtering out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improving alarm accuracy.

# **Face Recognition**

Dahua Face Recognition technology extracts the features of captured faces and compares them with that in face database to recognize the person identity.

#### **SMD Plus**

With intelligent algorithm, Dahua Smart Motion Detection technology can

- · 32/64 Channel IP video access
- Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- Up to 16 Channel perimeter protection
- Up to 4 Channel video stream face recognition
- Up to 22 face pictures/sec processing
- Up to 20 face databases with 100,000 face images in total



categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

#### Video Metadata

With deep learning algorithm, Dahua Video Metadata technology can detect, track, capture vehicle, non-motor vehicle and people, and select the best images, and extract attributes.

# **ANPR by Camera**

With deep learning algorithm, Dahua ANPR technology can recognize the number plate information of vehicles in the image with ANPR cameras. Support block/allowlist mode, searching target vehicles from recorded video.

### **Fisheye Dewarping**

Fisheye dewarping solves the problem of distortion in the circular panoramic view. The device offers various dewarping modes for different installations and configurations that enhance the video, in both live or playback modes. Each dewarping mode offers options to adjust each scene.

#### **People Counting by Camera**


With deep learning algorithm, Dahua People Counting technology can track and process moving human body targets to realize the accurate statistics of enter No., leave No., and In Area No. Working with management platform, it outputs yearly/monthly/weekly/daily reports to meet your requirements.

# Stereo Analysis by Camara

With deep learning algorithm and scene 3-dimensional information, Dahua Stereo Analysis technology can recognize people's behaviors, such as fall detection, violence detection, strand detection, and space exception, and then generates alarm signals and triggers linkage.







Technical Specification		Resolution	16MP, 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1 etc.		
System		Record Mode	Manual, Schedule (Continuous, MD (Motion Detection), Alarm, IVS)		
Main Processor	Multi-core embedded processor  Embedded LINUX	Record Interval	1–120 min (default: 60 min), Pre-record: 1–30 sec, Post-record: 10–300 sec		
Operating System		Raid Support	Raid0,Raid1,Raid5,Raid10		
Perimeter Protection		Video Detection and	Video Detection and Alarm		
Performance	16 channel, 10 IVS rules for each channel	Trigger Events	Alarm Out, Video Push, Email, Recording, PTZ, Tour,		
Object classification	Human/Vehicle secondary recognition for tripwire and intrusion		Snapshot, Voice Prompt, Buzzer and Screen Tips  Motion Detection, MD Zones: 396 (22 × 18), Video Loss,		
Al Search	Search by target classification (Human, Vehicle)	Video Detection	Tampering and Scene Change		
Face Recognition		Alarm input	16 Channel		
Performance	Max 22 face pictures/sec processing (modeling and comparing)	Relay Output	6 Channel		
	4 channel video stream face recognition/16 channel picture stream face recognition (with FD camera)	Playback and Backu	Playback and Backup		
Character Manda	Detect strangers' faces (not in device's face database).	Sync Playback	1/4/9/16		
Stranger Mode	Similarity threshold can be set manually.  Up to 8 target face images search at same time, similarity	Search Mode	Time/Date, Alarm, MD and Exact Search (accurate to second)		
Al Search	threshold can be set for each target face image.	Backup Mode	USB Device/Network		
Database Management	Up to 20 face databases with 100,000 face images in total. Name, gender, birthday, nationality, address, ID	Third-party Support			
Database Application	information can be added to each face picture.  Each database can be applied to video channels independently.	Third-party Support	Panasonic, Sony, Samsung, Axis, Pelco, Arecont, Onvif, Canon and more		
T: 5 .	independently.  Buzzer, Voice Prompts, Email, Snapshot, Recording,	Network			
Trigger Events	Alarm Out, PTZ Activation, etc.	Interface	2 RJ-45 Ports (10/100/1000 Mbps)		
Metadata		PoE	N/A		
Face	Gender, age, glasses, beard, mouth mask, expression.		HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm		
Vehicle	Plate No., type, color, vehicle type, logo, plate color, ornament, calling, seatbelt, region.	Network Function	Server, IP Search (Support Dahua IP camera, DVR, NVS, etc.), P2P		
Human Body	Top, top color, bottom, bottom color, hat, bag, gender,	Max. User Access	128 users		
·	age, umbrella.	Mobile App	iPhone, iPad, Android		
Non-motor Vehicle	Type, color, number of passengers, helmet.	Interoperability	ONVIF 2.4, SDK, CGI		
Al Search	Support search target video by metadata.	Storage	Storage		
Audio and Video	udio and Video		8 SATA III ports, up to 10 TB for a single HDD. The		
IP Camera Input	32/64 Channel	Internal HDD	maximum HDD capacity varies with environment temperature		
Two-way Talk	1 Channel Input, 1 Channel Output, RCA	eSATA	1 eSATA		
Display		Auxiliary Interface	Auxiliary Interface		
Interface	2 HDMI, 1 VGA	USB	4 USB Ports (2 Rear USB 3.0, 2 Front USB 2.0)		
Resolution	HDMI1/VGA: 1920 × 1080, 1280 × 1024, 1280 × 720	RS232	1 Port, for PC Communication and Keyboard		
	HDMI2: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720	RS485	1 Port, for PTZ Control		
Decoding Capability	4-ch@8MP (30fps), 16-ch@1080P (30fps)	Electrical			
Multi-screen Display	1st Screen: 1/4/8/9/16/25/36	Power Supply	Single, AC100V–240V, 50–60 Hz		
Recording	2nd Screen: 1/4/8/9/16	Power Consumption	NVR: <16.1W (Without HDD)		
Bandwidth	320 Mbps (160 Mbps when Al function enabled)	Fan	Smart fan, automatically adjust running speed		
		Environmental			
Compression	Smart H.265+/H.265/Smart H.264+/H.264/MJPEG	Operating Conditions	-10°C to +55°C (+14°F to +131°F), 86–106kpa		



# **Wiz Mind** | DHI-NVR5832/5864-I

Storage Conditions	0°C to +40°C (+32°F to +104°F), 30–85% RH			
Construction				
Dimensions	2U, 439.7 mm $\times$ 451.0 mm $\times$ 94.9 mm (17.31" $\times$ 17.75" $\times$ 3.73")			
Net Weight	6.70 kg (14.8 lb) (without HDD)			
Gross Weight	9.30 kg (20.5 lb) (without HDD)			
Certifications				
CE	EN55032, EN55024, EN50130-4, EN60950-1			
FCC	Part 15 Subpart B, ANSI C63.4-2014			
UL	UL 60950-1			

UL	UL 60950-1			
Ordering Information				
Туре	Model	Description		
32/64 Channel WizMind NVR	DHI-NVR5832/5864-I	32/64 Channel 2U WizMind Network Video Recorder		

# Dimensions (mm[inch])

