

DHI- NVS0104/0204/0404HDC

Network Video Server



- > H.264+/H.264 dual-stream video compression
- > Support HDCVI/AHD/TVI/CVBS/IP video inputs
- > Support built-in 2.4G/5G Wi-Fi module and 4G module
- > Support high quality two-way talk
- > Support Micro SD card, maximum support 128G
- > 1/2/4 channel video and audio inputs



System Overview

Dahua as a technology leader, is always the first ever developed the shining new technology in the security industry, and today we present a new generation of NVS. As the perfect solution to upgrade existing video surveillance systems, NVS0104/0204/0404HDC supports penta-brid access technology such as HDCVI, AHD, TVI, CVBS and IP to effortlessly integrate with popular industry formats, offering an affordable solution loaded with flexible options.

Designed as a full compatibility product, this NVS is able to provide end user the simplicity of analog system, namely lower system cost, simple installation and use of existing cable. It is ideal for a wide range of applications such as public safety, retail store, transportation, home protection and education.

Functions

Smart H.264+

Smart Codec, H.264+ can reduce up to 70% bit rate and storage requirements without having to invest in new cameras.

HDCVI/AHD/TVI/CVBS Auto-detect

The NVS can auto recognize the signal of front-camera without any setting. It makes operation more friendly and convenient.

Built-In WiFi/4G Module

The NVS can be equipped with built-in 2.4G/5G Wi-Fi module or 4G module.

Intelligent Video System (IVS)

With built-in intelligent video analytics, the NVS has the ability to detect and analyze moving objects for improved video surveillance. The NVS provides optional standard intelligence at the edge allowing detection of multiple object behaviors such as abandoned or missing objects. IVS also supports Tripwire analytics, allowing the camera to detect when a predetermined line has been crossed.





DHI-NVS0104/0204/0404HDC

Technical Specific	ation	Network	1 RJ45 Port, 10M/100M self-adaptive Ethernet interface
System		RS485	1 Port, for PTZ Control
Main Processor	Embedded Processor	RS232	1 Port, for PC Communication and Keyboard
Operating System	Embedded LINUX	4G	built-in module(Optional)
Operation Interface	No local interface, operate on web	2.4G/5G Wi-Fi	built-in module(Optional)
Recording		Indicator Light	ACT/NET/ALM/VIDEO
Video Compression	H.264+/H.264	Antenna interface	1 Port, for built-in wireless module
Audio Compression	G.711A, G.711U, PCM	General	
		Power Supply	DC12V/2A
Video		Power Consumption	<10W (Without HDD)
HDCVI Camera Input	1/2/4 Channel, BNC	Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa
IP Camera Input	1/2/4 Channel, each channel up to 5MP	Storage Conditions	0°C ~ +50°C (+32°F ~ +122°F), 0 ~ 90% RH
Video Out	1 TV Out, reuse Audio Out	Dimensions	136mm×162mm×30mm (5.4" x 6.4" x 1.2")
Resolution	1080P, 1080N, 720P, 960H, D1, HD1, BCIF, CIF, QCIF	Net Weight	0.57kg (1.26lb)
Resolution	Main stream: NVS0104/0204HDC: 1080P/720P/960H/D1/HD1/BCIF/CIF/ QCIF (1~25/30fps) NVS0404HDC: 1ch*1080P(1~25/30fps)+3ch*1080P(1~15fps); 4ch*1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) Sub steram:CIF/QCIF(1~25/30fps)	Gross Weight	1kg (2.2lb)
Record Rate		Installation	Desktop installation
		Certifications	
		Certifications	FCC: Coming soon
Bit Rate	1Kbps ~ 6144Kbps Per Channel		UL: Coming soon
Dit Nate			
Record Mode	Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop		
Record Interval	$1{}^{\sim}60$ min (default: 60 min), Pre-record: $1{}^{\sim}30$ sec, Post-record: $10{}^{\sim}300$ sec		
Privacy Masking	With an any size area for shelter protection in full screen, 4 rectangular zones (each camera)		
Audio			
Audio In	1/2/4		
Audio Out	1		
Two-way Talk	1 Mic In, reuse Audio Out		
Sample Rate	8KHz, Two-way Talk(48KHz)		
Bit Rate	64Kbps, Two-way Talk(384Kbps)		
Storage			
Storage Mode	Micro SD		
	Network		
Interface			
SD	1 Port		

TIDMS

Alarm In/Out

4/2


DHI-NVS0104/0204/0404HDC

Ordering Information			Front Panel	
Туре	Part Number	Description		
1 Channel NVS	DHI-NVS0104HDC	1 Channel Network Video Server		
2 Channel NVS	DHI-NVS0204HDC	2 Channel Network Video Server		
4 Channel NVS	DHI-NVS0404HDC	4 Channel Network Video Server	Rear Panel	

DHI-NVS0104HDC

Dimensions (mm)












DHI-NV\$0204HDC



DHI-NVS0404HDC





Rev 001.001 © 2016 Dahua . All rights reserved. Design and specifications are subject to change without notice.

